





LJ3055 PORTABLE JAW CRUSHING PLANT

The 3055 jaw crushing plant is the newest jaw crusher in the Lippmann product line. Featuring an opposing wedge design, it is perfectly suited for any size job. The chassis has been created to accept any application you require—hopper removable system, extended discharge conveyor to feed secondary or screen plant, diesel or electric, hydraulic dump grizzly, cross conveyor, hydraulically folding hopper extensions.

- An extra heavily ribbed steel frame—stress relieved after welding and before machining
- One piece steel pitman
- Heat-treated forged alloy steel eccentric shaft
- Oversized roller bearings on the pitman
- Spherical roller bearings on the frame
- Reversible manganese steel jaw dies and extensions
- Steel cheek plates
- Opposing wedge toggle tensioning system
- Grease lubricated
- Two heavy-duty flywheels, one grooved for V-belts



SPECIFICATIONS

Jaw Crusher	30"x55"	Horsepower		Transportation (lbs)	
RPM	250	Jaw Crusher	200	Tires	315/80R22.5
Stroke	3/4"	Autolube	1	Rear axle	71,000
Feed Size	27"	Opposing Wedge	1	King Pin	55,750
Discharge Conveyor	54"	Feeder	40	Total	126,750
Operating Speed	318	Discharge Conveyor	(2) 15	Weight of Feeder Module	69,250
Feeder	55"x20'			Total Weight	166,250
Operating Speed	830 Max				
Grizzly Length	5'				

Hydraulic toggle or Manual toggle plate available
 *Manual toggle plate option only
 Closed Side Setting (CSS) inches

2	2.5	3	3.5	4	4.5	5
-	-	250	288	345	400	420
6	7	8	10	12	14	-
500	600	*720	-	-	-	-

ADDITIONAL OPTIONS

Hydraulic leveling jacks - (4) 70,000lb
 Six (6) Run-On Jack Legs

NEMA - 12 motor control center
 Cross conveyor under grizzly

Hydraulic folding hopper extensions
 Tire bulkheads