

**GT-3400**  
Sidemounted Trimmer



**GOMACO**<sup>®</sup>

*The Worldwide Leader in Concrete Paving Technology*

# A Time-Saving Attachment for the GT-3400 Trimmer

There was so much success with the GOMACO GT-3400 trimmer, that a customer immediately began working with GOMACO on a new type of trimmerhead attachment for the machine. An attachment was created for the trimming of narrower widths for scab-on curb and gutter slipforming applications.

The GT-3400 trimmer's new sidemounted trimmerhead attachment has a powerful, closed-loop trimmer that is 30 inches (762 mm) wide and has a wheel diameter of 56 inches (1422 mm). It features framework on the front to support the trimmerhead. The new trimmer has 18 inches (457 mm) of hydraulic vertical lift for depth adjustments and for easy shipping on a trailer. It also has a third conveyor for moving material.

The extra conveyor transfers the trimmed material from the trimmerhead to the standard transfer conveyor. The contractor put their GT-3400 trimmer with the new sidemounted trimmerhead to work on its first project in Canada. It was trimming between six to

10 inches (152-254 mm) deep, 19 inches (483 mm) below the existing grade, and 30 inches (762 mm) wide against the existing roadway.

Production averaged up to six feet per minute (1.8 mpm) on the first trimming pass. It's capable of trimming accurate grade in just one hour's time, what would normally take all day with a backhoe. Its zero-clearance capabilities were useful as it trimmed by several utility poles and other obstacles along the existing roadway.



CG-081505-D4

The blade on the trimmerhead was used to level the CTB material for final grade.



CG-081512-D5

The 30 inch (762 mm) wide trimmerhead cuts 19 inches (483 mm) below grade on its first project.

Cover Photo: CG-081510-D9

Manufactured under one or more of the following U.S. or foreign patents: 5,924,817; 5,941,659; 6,099,204; 6,450,048; CA2,211,331; 7,044,680; 7,284,472; 7,517,171; 7,845,878; 7,850,395; CA2,864,902; CA2,591,177; 8,855,967; 8,682,622; 9,051,696; 9,180,909; 9,200,414; and patents pending.

GOMACO and G+ are registered trademarks of GOMACO Corporation.

GOMACO Corporation reserves the right to make improvements in design, material, and/or changes in specifications at any time without notice and without incurring any obligation related to such changes. Performance data is based on averages and may vary from machine to machine.

Printed in U.S.A. © 2016 (1 GOMACO Corp.)



4899 W 2100 S  
Salt Lake City Utah 84120

800-779-4450  
[www.icmsolutions.com](http://www.icmsolutions.com)



*The Worldwide Leader in Concrete Paving Technology*



GOMACO Corporation's Quality Management System Is ISO 9001 Certified By The American Systems Registrar.

Quality Policy: We Shall Meet Or Exceed Our Customers' Expectations.

