

COMMANDER III
TRIMMER



GOMACO[®]

The Worldwide Leader in Concrete Paving Technology

- High-Production with the Commander III Trimmer -



CG-101432 D1

The Commander III trimmer is equipped with a powerful trimmerhead with 114 horsepower (85 kW) of the total power of the engine dedicated to it.



CG-101426 D7

It is capable of trimming flat or monolithic sidewalk profiles up to 11 feet (3.4 m) wide.



CG-101426 D11

The transfer conveyor has seven feet (2.1 m) of sliding capabilities to place the material over the stringline or into the center of the road.

- High-production trimmer capable of widths up to 11 feet (3.4 m)
- Features the same framework as the Commander III curb and gutter model, but with minor modifications
 - Right, front track has been switched to a pivoting front track to accommodate zero trimmerhead clearance on both sides
 - Front tracks are parallel and trimmerhead is undermounted
 - Vibrator hydraulics for paving applications removed and replaced with a bigger, closed-loop trimmer pump for more power
- Equipped with the most powerful trimmer ever put on a Commander III
 - 114 horsepower (85 kW) of the total engine power dedicated to the trimmer
- Capable of trimming flat or monolithic sidewalk and curb and gutter profiles
- Trimmerhead has three air shocks to keep it stable during the trimming process
 - If it would hit a large rock or other object, the air shocks reduce some of the force of impact into the Commander III's mainframe
- Two conveyors move the material
 - Transfer conveyor moves material from the trimmerhead on the front of the machine towards the discharging conveyor in back
 - Each belt is 11 feet (3.4 m) long and 20 inches (508 mm) wide
 - Discharge conveyor has seven feet (2.1 m) of sliding capabilities to place material over the stringline or discharge into the center of the roadway
- Shipping width is only 11 feet (3.4 m) and the Commander III trimmer transports as a single unit
- Trimming conversion can be retrofitted to higher horsepower existing new generation Commander IIIs with G21 or newer GOMACO control systems

Front Cover: CG-101432 D13

MANUFACTURED UNDER ONE OR MORE OF THE FOLLOWING U.S. OR FOREIGN PATENTS: 5,190,397; 5,209,602; 5,924,817; 5,941,659; 6,099,204; 6,450,048; 2,211,331; 2,069,516; 7,044,680; 7,284,472; 7,517,171; 7,845,878; 7,850,395; 8,855,867; AND PATENTS PENDING.

GOMACO Corporation reserves the right to make improvements in design, material, and/or changes in specifications at any time without notice and without incurring any obligation related to such changes. Performance data is based on averages and may vary from machine to machine.

Printed in U.S.A. © 2014 (11GC) GOMACO Corp.



The Worldwide Leader in Concrete Paving Technology



4899 W 2100 S
Salt Lake City Utah 84120

800-779-4450
www.icmsolutions.com



GOMACO Corporation's Quality Management System ISO 9001 Certified By The American Systems Registrar.

Quality Policy: We Shall Meet Or Exceed Our Customers' Expectations.

