

# HAWKEYE SCREED



The GOMACO Hawkeye Screed is designed for finishing a variety of projects including driveways, streets, ramps, or any flat slab. The truss system on the MV-18 model is manufactured out of high tensile tubular steel in an 18 in. (457 mm) equilateral triangle. This screed is built to last in concrete job-site conditions.



## **GOMACO**

The Worldwide Leader in Concrete Paving Technology



# HAWKEYE SCREED SPECIFICATIONS

- Hawkeye screed model MV-18 is an engine-powered screed that eliminates the need for an air compressor on the job site. It is equipped with an 8.5 hp (6.3 kW) gasoline engine.
- Truss sections for the MV-18 screed are available in 5 ft. (1.52 m) and 7.5 ft. (2.29 m) lengths. All sections feature rigid stainless steel finishing screeds.
- Two 2500 lb. (1134 kg) capacity hand winches are included and 65 ft. (19.81 m) of 1/8 in. (3.2 mm) diameter aircraft cable with necessary pulleys and hooks. Optional hydraulic powered or air-powered winches are available.
- Crowning connectors and locknuts are electroplated to prevent rust and corrosion. They are accurately machined to assure positive crown adjustment, uniform grade control and easy assembly.
- The MV-18 can accommodate both winches at one end, allowing one man to move the screed forward.
- The MV-18 includes a 3/4 in. (19 mm) rustproof vibrator shaft with ball bearings on 30 in. (762 mm) centers.
- Eccentric weights clamp on the shaft. Heavier weights for finishing low-slump concrete are easily installed without disassembly of the line shaft.
- The standard width of the MV-18 screed is 11.5 ft. (3.51 m) and weighs 312 lbs. (141.5 kg). The maximum frame width is 49 ft. (14.94 m).
- The optional AV-18 is 12.5 ft. (3.81 m) wide and weighs 270 lbs. (122.5 kg).



Visit our web site at [www.ICMSolutions.com](http://www.ICMSolutions.com)

Cover Photos: Top Photo, CG-089420-3AX; Bottom Photo, 51-85-7-A-O

Manufactured under one or more of the following U.S. or foreign patents: 6,450,048; 7,044,680; 7,284,472; 7,517,171; 7,845,878; 7,850,395; CA2,864,902; CA2,591,177; 8,855,967; 8,682,622; 9,051,696; 9,180,909; 9,200,414; 9,404,228; 9,428,869; 9,458,581; 9,464,716; 9,541,195; 9,567,715; 9,624,626; 9,637,872; 9,644,328; 9,633,162; 9,670,627; 9,739,019; 9,764,762; 9,869,063; 9,982,399; 9,963,836; 10,005,489; 10,206,016; AU2018100400; AU2019100743; and patents pending.

GOMACO Corporation reserves the right to make improvements in design, material, and/or changes in specifications at any time without notice and without incurring any obligation related to such changes.

Printed in U.S.A. © 2020 (4-GC) GOMACO Corporation Order #0320-0A10135



[www.icmsolutions.com](http://www.icmsolutions.com)  
4899 W 2100 S  
Salt Lake City Utah 84120

800-779-4450



*The Worldwide Leader in Concrete Paving Technology*

GOMACO Corporation's Quality Management System Is  
ISO 9001 Certified By The American Systems Registrar.

Quality Policy: We Shall Meet Or  
Exceed Our Customers' Expectations.

